

Type code for industrial thermometers

VTE2	4	1. Type	version									
		1	TRA-W 10	"cable, plug-in" (RKS)	4	TRA-W 40	"cable, surface", (RZS)	7	TRA-W 70	"cable, bayonet", (RTS)		
		2	TRA-W 20	"cable, surface", (RYS)	5	TRA-W 50	"cable, screw-in", (RLS)	8	TRA-W 80	"harsh cable plug-in)		
		3	TRA-W 30	"cable, surface", (RYT)	6	TRA-W 60	"oil-tight surface", (RLO)	A	TRA-W 90	"high temp. Cable plug-in), (RMK)		
		2. Certificate										
		0	without									
		1	Simpel Apparatus according to ATEX directives									
		3. Cable material										
		1	PVC	70°C	3	MFA / PFA	200°C	5	ELAX / PTFE	105°C 4-wire		
		2	Silicon	150°C	4	ETFE / KAPT	150° 4-wire	6	TPEV	105°C 4-wire		
		4. Measuring insert = sensor / wiring										
		1	1x Pt100	2-wire	4	2x Pt100	2-wire	M	1x Pt1000	3-wire		
		2	1x Pt100	3-wire	5	2x Pt100	3-wire	N	1x Pt1000	4-wire		
		3	1x Pt100	4-wire								
		5. Measuring insert / tolerance class										
		2	Cl. A	TF	(tolerance class -30 ... +300°C)			4	Cl. A	WW	(tolerance class -100 ... +450°C)	
		6. Thermowell material										
		1	1.4404	316L	2	Brass		3	Copper		4	PTFE/Copper
		7. Protection tube size										
		0	Ø 3 x 0,5 mm		4	Block 5 x 5 x 25 mm		7	Bolt M6		A	Ø 6 x 12,9 mm SS
		1	Ø 6 x 0,5 mm		5	Block 26 x 18 x 50 mm		8	Bolt M8		P	Form 4, Ø24 mm
		2	Ø 8 x 0,5 mm		6	Block 8 x 10 x 40 mm						
		8. Process connection										
		0	without									
		1	Compression fitting G1/8" SS			5	Mounting Band, DN300 (1000 mm)					
		2	Compression fitting G1/4" SS			7	Bayonet fitting M12x1					
		3	Compression fitting G1/2" SS			8	Bayonet fitting M12x1,75					
		4	Compression fitting G1/4" Brass			S	Compression fitting 1/2" NPT SS					
					F	Mounting flange						
		9. Thermowell										
		0	without									
		1	tube G1/2	Ø 8 x 1 L=75 mm	2	tube G1/2	Ø 8 x 1 L=175 mm	3	tube G1/2 Ø 8 x 1 L=275			
		10. Immersion length										
		0	13,5 mm		5	30 mm		C	200 mm		M	Form 4 D1 140/65 mm.
		2	15 mm		6	50 mm		D	300 mm		N	Form 4 D2 200/125 mm
		3	20,2 mm		A	100 mm		E	400 mm		P	Form 4 D4 200/65 mm
		4	25 mm		B	150 mm		F	500 mm		R	Form 4 D5 260/125 mm
		11. Cable length										
		1	0,5 m		6	4,0 m		C	9,0 m		H	25 m
		2	1,0 m		7	5,0 m		D	10,0 m		K	30 m
		3	1,5 m		8	6,0 m		E	12,0 m		L	40 m
		4	2,0 m		A	7,0 m		F	15,0 m		M	50 m
		5	3,0 m		B	8,0 m		G	20,0 m		Z	customised lengths
		13. Type of connection / rail mounted transmitter										
		0	without									
		L	with rail mounted transmitter			//	APAQ R130	Basic, RTD				
		A	with rail mounted transmitter			//	IPAQ-4L	Universal, 90 - 250 VAC				
		B	with rail mounted transmitter			//	IPAQ-4L	Universal, 20 - 30 VDC				
		C	with rail mounted transmitter			//	IPAQ R330	Universal [Ex]				
		H	with rail mounted transmitter			//	IPAQ R520	Smart, HART, SIL2 [Ex]				
		M	with rail mounted transmitter			//	IPAQ R530	Smart, HART [Ex]				
		14. Measuring range										
		0	without									
		1	Customized Configuration			3	-50...+100°C			6	0...+100°C	
		2	-50...+50°C			4	-50...+150°C			7	0...+150°C	
					5	0...+50°C			8	0...+200°C		
		15. Calibration report										
		0*	without									
		Sensor calibration										
		1	1-point (single) room temperature									
		P	2-point (single) 0°, 100°C									
		R	2-point (double) 0°, 100°C									
		2	2-point (single) 0%, 100% of range									
		3	2-point (double) 0%, 100% of range									
		S	3-point (single) 0°, 50°, 100°C									
		T	3-point (double) 0°, 50°, 100°C									
		4	3-point (single) 0%, 50%, 100% of range									
		5	3-point (double) 0%, 50%, 100% of range									
		6	customised (single)									
		7	customised (double)									
		Sensor + Transmitter calibration										
		A	2-point (single) 0%, 100% of range									
		B	3-point (single) 0%, 50%, 100% of range									
		C	5-point (single) 0%, 25%, ..., 100% of range									
		Sensor + Transmitter calibration with error correction										
		E	2-point (single) 0%, 100% of range									
		F	3-point (single) 0%, 50%, 100% of range									
		G	5-point (single) 0%, 25%, ..., 100% of range									
		H	customised									

Vissa kombinationer är inte möjliga. Vänligen kontakta KROHNE Inor för ytterligare information.

